




Doppie Retransfer



The **NEW DOPPIE** Retransfer printer delivers top quality 600 dpi, 24-bit colour prints at high speed - over 160 cards/hour! The 600dpi printing technology gives a clear, crisp print even for fine lines and tints.

Retransfer printing technology allows printing of high-quality, full-bleed ID cards in brilliant true colour. The retransfer process uses dye sublimation technology to print a high-resolution image in reverse directly onto the film base. The printer then thermally transfers the image and film onto the card surface through heat and pressure, thermally bonding it to the card.

Features:

- High-speed printing - over 160 cards per hour*
- Full colour printing
- Over the edge printing on CR-80 cards
- 600 dpi dye-sublimation printing technology
- Industry-leading 24-bit continuous tone printing
- Single and double-sided printing
- Quick change ribbon cassette
- Vista, Win 7 (32 and 64 bit) driver

Available Options:

Inline contact and/or contactless encoder

IDENTILAM
thebadgingcompany

www.identilam.co.uk +44 (0)1293 854 700

John Bostock House, Faygate, Horsham, West Sussex RH12 4DN



Print	Print method Resolution Input Output Printing area	Dye sublimation retransfer printing 600DPI R/G/B 256 level Y/M/C/UV 256 level Over the edge on CR-80 cards
Speed	Printing speed (Single printing: YMCK) Printing speed (Double printing: YMCKK)	More than 22.5s full colour YMCK (160 cards / hr) More than 36s full colour YMCKK (100 cards / hr)
Capacity	Feeder capacity Card exit capacity	250 cards (if card thickness is 0.76mm) 250 cards (if card thickness is 0.76mm)
Card	Card thickness Card size Card material	0.25 to 1.0 mm CR-79 & CR-80 PVC, PET, PC, ABS (Except PVC cards need prior confirmation)
Display	Display	LCD panel (with back light), LED, Operation
Size	Dimensions Weight	421 x 271 x 331mm 15kg
Power	Power consumption	Less than 3A (100V)
Temperature	Operating temperature	10 to 35°C - 20 to 80% humidity
Ribbon**	Ribbon capacity Film ribbon	500 images / roll (YMCK) Clear Retransfer, Holographic Retransfer
	Ink ribbon	YMCK, YMCKK, YMCKHs (except for PVC Card) YMCKP (for smart card), YMCCK (UV ink)
Driver	Drivers Interface	XP, Vista, Win 7 (32 & 64 bit) USB and Ethernet
Warranty**	Printer Print head	2 year return to factory service printer warranty Limited lifetime
Other	Extendibility Memory size	2 USB HUBS (inside printer) 64MB
Options	Laminator Encoder	Dedicated transfer laminator available Contact Encoder, Contactless Encoder